

Acoustic Panel dukta[®] JANUS

Material: 3-layered panel spruce (27mm), MDF natural (25mm)
 Special material: _____
 PEFC-certified without certification

Surface: unlacquered
 lacquered transparent lacquered white RAL9010, lacquered grey RAL7000
 lacquered black RAL9005, lacquered Special color: _____

All coatings are 2-component coatings based on acid-hardening melamine resin and meet the requirements of the standard DIN EN71-Part 3

Panel dimensions: Standard: 2500 x 1020 x 27 (25) mm

Packaging unit: Standard: 1 panel = 2.55m²

Useable surface: the milled surface is: 2375 x 966 mm

Bend radius: ca. ≥ 100 mm

Weight:/m² 7-10 kg (depending on Material)

Venting: ca 33%

Composition: without fleece

Installation type: horizontal or vertical on walls or ceilings, freestanding

Mounting: using Kolar accessories (please see below)

Application: Wall cladding, ceilings, furniture, room partitions, ...

Manufacturer: Franz Kolar GmbH, www.kolar.at

Product offered: _____

Amount: _____ m²

Please Note

To prove that products made from PEFC-certified / FSC-certified material are delivered to you, you must indicate when ordering that you are require a material to include this certificate. A later request for a certificate is not possible on goods which have already been ordered or delivered.

dukta[®] Assembly Accessories for JANUS

End profile (floor and edges):

With frame- End profile straight

Item: DU.AL07

With frame- End profile bent, outside radius 610 mm

Item: DU.AB07-610

With frame- End profile bent, outside radius 310mm

Item: DU.AB07-310

Without frame – End profile straight

Item: DU.AL05

Without frame – End profile bent, outside radius 603mm

Item: DU.AB05-603

Without frame – End profile bent, outside radius 303mm

Item: DU.AB05-303

Metal base, ground stainless steel, 327x60x121mm

As of November 2018